

Volume 24(2),

December, 1996

ISSN 0250-5363




KARACHI UNIVERSITY JOURNAL OF SCIENCE

University of Karachi
Karachi, Pakistan

Gait Analysis using Moiré Fringe Topography and Rasterstereography (Simultaneous Recording)

The bipedal locomotion is in some ways the simplest and at the same time the most difficult form of human locomotion to control. The simplicity arises from the fact that the legs are activated out of phase with one another in each step, as in walking. The complexity of bipedal locomotion arises from the relatively unstable equilibrium that occurs, even when standing on two legs. This state is like an inverted pendulum. The feet provide a narrow base of support for the body's center of mass. Small displacements forward or backward can be compensated by reflexes activated, for example, by stretching the ankle extensors or flexors. Normal gait of a human being is, always, in the sagittal plane. The flexing and the extending of arms and legs, which cause the body to move, also, occur in the same plane. Normal gait is, thus, a combination of flexion and extension.



Right Leg	Left Leg
Step 1: Right leg forward, left toe and right heel touching the ground; center of gravity lying between the two feet <i>Hip</i> Extension <i>Knee</i> Extension <i>Ankle</i> Dorsiflexion Mirror Image of Step 4; identical to Step 7	Extension Extension Planter Flexion
Step 2: Right leg forward, right toe and right heel (that is, the right foot) touching the ground as well as left toe on ground <i>Hip</i> Extension <i>Knee</i> Flexion <i>Ankle</i> Neutral Mirror Image of Step 5	Extension Flexion Neutral
Step 3: Left foot in air (moving forward), body supported by right foot only, center of gravity lying on top of right foot <i>Hip</i> Flexion <i>Knee</i> Flexion <i>Ankle</i> Neutral Mirror Image of Step 6	Flexion Flexion Neutral
Step 4: Left leg forward, right toe and left heel touching the ground; center of gravity lying between the two feet <i>Hip</i> Extension <i>Knee</i> Extension <i>Ankle</i> Planter Flexion Mirror Image of Step 1	Extension Extension Dorsiflexion
Step 5: Left leg forward, left toe and left heel (that is, the left foot) touching the ground as well as right toe on ground <i>Hip</i> Extension <i>Knee</i> Flexion <i>Ankle</i> Neutral Mirror Image of Step 2	Extension Flexion Neutral
Step 6: Right foot in air (moving forward), body supported by left foot only, center of gravity lying on top of left foot <i>Hip</i> Flexion <i>Knee</i> Flexion <i>Ankle</i> Neutral Mirror Image of Step 3	Flexion Flexion Neutral
Step 7: Right leg forward, left toe and right heel touching the ground; center of gravity lying between the two feet <i>Hip</i> Extension <i>Knee</i> Extension <i>Ankle</i> Dorsiflexion Identical to Step 1	Extension Extension Planter Flexion



Syed Arif Kamal, Amir Salim Choudhry
and Yonus Ali Siddiqui

GAIT ANALYSIS USING MOIRE FRINGE TOPOGRAPHY AND RASTERSTEREOGRAPHY (SIMULTANEOUS RECORDING)

SYED ARIF KAMAL¹, A. S. CHOUDHRY AND Y. A. SIDDIQUI

Department of Mathematics, University of Karachi, Karachi-75270 (Pakistan)

ABSTRACT

Moiré fringe topography and rasterstereography are noninvasive 3-D optical imaging techniques. They provide height and curvature maps of three-dimensional objects respectively. In gait analysis and other movement activities the same position cannot be reproduced again. It is desired to record heights and curvatures of human trunk (e.g. selected points on human back) at the same time. A technique for simultaneous moiré and raster recording is introduced using selective filtering.

Keywords: Moiré fringe topography, rasterstereography, motion analysis, optical filtering

INTRODUCTION


Throughout the course of history, man has performed measurements by eye estimate, tape, and calipers to describe the form of the human body. Over 4000 years ago Egyptian artists set up a system of measurement based on the width of a human hand.

The need to find a convenient three-dimensional measuring system led to the development of photogrammetry in the middle nineteenth century. Medical photogrammetry is the term used to cover all applications of photogrammetry in the broad field of medicine. These include stereophotogrammetry, holography, integrated surface imaging system (ISIS), 3-D video laser scanning system, moiré fringe topography and rasterstereography.

We are in need of methods which are inexpensive, easy to implement, simple to be performed by moderately trained personnel and elegant enough to permit handling by various algorithms. Moiré fringe topography and rasterstereography have all these characteristics. The first one provides height maps and the second one curvature maps. If we are able to record and process information from both these techniques we may obtain a complete profile of human trunk during every cycle of gait. Such information may be used in modeling of human gait and understanding of various neurological disorders.

Moiré Fringe Topography

Moiré fringes are a series of interference fringes arising from the superposition of sets of parallel lines or threads, the sets being slightly inclined to one another. Width of the lines of the grid should be equal to the space between them. The shadow type moiré topography apparatus used in the

¹PhD (Neuroscience); MA, Johns Hopkins, Baltimore, MD, United States; MS, Indiana, Bloomington, IN, United States; Sessional Faculty, the Aga Khan University Medical College, Karachi • *paper mail:* Associate Professor, Department of Mathematics, University of Karachi, PO Box 8423, Karachi 75270, Sindh, Pakistan • *telephone:* +92 21 9926 1300-15 ext. 2293 • *e-mail:* profdrakamal@gmail.com • *homepage:* <https://www.ngds-ku.org/kamal>  0000-0002-1711-4827

pitch of the projected grid matched with the pitch of the deformed grid. Formulae to calculate the distances are listed in appendix-A.

Rasterstereography

Rasterstereography is very similar to stereophotography. The difference is that one of the cameras is replaced by a slide projector and a raster (Fig. 3b) is projected on the body. Because of the curvature of the body the raster is distorted. Study of this distortion provides information about the topological properties of the surface under study (Hierholzer & Frobin, 1981). The remarkable feature of rasterstereography is that it does not require a specific arrangement of the apparatus to obtain meaningful rasters, whereas only a specific geometry of the moiré set up would provide contours with desired mathematical properties.

Consider a raster projected on a cylindrical surface. Let us take x and z axes parallel to each set of parallel lines (grids) of raster pattern. Let the cylinder be aligned in such a way that its axis coincides with the z axis. Using cylindrical coordinates (ρ, ϕ, z) let us describe the cylinder as the volume enclosed by intersection of the surfaces $\rho = \rho_0, z = 0, z = z_0$. Note that the curved surface of the cylinder has two curvatures at every point. The curvature corresponding to the curve defined by intersection of the surfaces $\rho = \rho_0, z = z_1, (0 \leq z_1 \leq z_0)$ is $\kappa_1 = 1/\rho_0$, whereas the curvature corresponding to the line defined by the intersection of $\rho = \rho_0, \phi = \phi_0 (0 \leq \phi_0 < 2\pi)$ is $\kappa_2 = 0$. The raster pattern projected on this cylinder shall be distorted. The lines parallel to z axis shall appear straight but their spacing shall not be uniform. From the variation of their spacing magnitude of κ_1 may be determined. To determine whether the surface is convex (positive curvature) or concave (negative curvature) one notes whether the spacing is increasing or decreasing towards the edges. If the surface is convex (concave) the spacing shall decrease (increase) when one moves away from the region under consideration. Further, the grids parallel to x axis shall converge (diverge) on moving away if the surface is positively (negatively) curved. A similar procedure applied to the other set of grids would give the local value of κ_2 . These simple ideas could be generalized for surfaces having other type of curvatures.




Fig. 1. Set-up for shadow type moiré fringe topography




Fig. 2. Moiré pattern of a normal spine

Therefore, we see that using a raster grid we may determine the curvatures κ_1 and κ_2 at any point. If curvatures at more than a few points are needed (e.g. curvature maps of the human trunk) algorithms must be developed to determine the curvatures from digitized data. Computing time may be minimized by using multigrid techniques. Where the variation of curvature is small a coarse grid may be used. For larger curvature variations a finer grid may be used (Stüben, 1992). Formulae to calculate curvatures from a rasterstereograph are listed in Appendix B.

THE HUMAN GAIT

The bipedal locomotion is in some ways the simplest and at the same time the most difficult form of locomotion to control. The simplicity arises from the fact that the legs are activated out of phase with one another in each step, as in walking.

The complexity of bipedal locomotion arises from the relatively unstable equilibrium that occurs, even when standing on two legs. This state is like an inverted pendulum. In a normal pendulum a displacement in either direction from its lowest point will produce a gravitational force that tends to restore the pendulum to this point. If the pendulum is inverted displacement of the weight from its highest point will produce a net gravitational force that will tend to displace the weight further. The feet provide a narrow base of support for the body's center of mass. Small displacements forward or backward can be compensated by the reflexes activated, for example, by stretching the ankle extensors or flexors. Appendix E explains the anatomical terms used in this discussion.

Once the body's center of mass has moved beyond the base of support provided by the feet the body shall fall forward (or backward) unless one limb is moved to provide a broader base of support in which the center of mass lies between the two feet. Walking is initiated by allowing the body to fall forward (generally by inhibiting activity in ankle extensors) to an unstable position and then moving one leg forward to re-establish equilibrium. Each step may, therefore, be considered as an unstable fall, followed by a return to a stable posture. In normal gait each limb alternately returns the body to stability. Steps involved in the gait of a normal person are shown in Fig. 4 and listed in Appendix C.

Normal gait of a human being is always in the sagittal plane. The flexing and extending of the arms and legs, which causes the body to move, also occurs in the same plane. Normal gait is thus a combination of *flexion* and *extension*.

3-D Optical Imaging in Gait Analysis

Moiré fringe topography is being widely applied in the detection (Adair, van Wijk & Armstrong, 1977), documentation (Willner, 1979), quantification (Kamal, 1983; 1987; 1996a,b) and follow-up (Kamal & Lindseth, 1980) of spinal deformities especially scoliosis (lateral curvature of the spinal column). It has also been used for the study of chest wall deformities (Shochat & Csongradi, 1983) as well as anthropometry (Windischbauer, 1983). Currently moiré topographs are also used to keep permanent records of patients suffering from rheumatic disorders as well as low back pain. Rasterstereography is also being applied selectively to monitor curvature of spinal column especially in scoliosis and kyphosis (Hierholzer & Frobin, 1981).

One of the areas in which moiré fringe topography and rasterstereography could be extremely useful is the study of gait. Preliminary studies of posture (Suzuki, Yamashita, Yamaguchi & Armstrong, 1981) and gait in normal subjects (Moreland & Lewis, 1981) and polio patients (Siddiqui & Choudhry, 1990) have already been performed. A study of posture and gait of patients suffering from neurological disorders, e. g. cerebral palsy would provide valuable insights into the mechanism of these disorders. Moiré and raster studies could also be supplemented by other techniques like edge- and intensity-based algorithms etc.

Movement on treadmill is not identical to natural, unhindered movement. For an understanding of gait pattern, natural walking must be studied. However, in natural walking distance of the subject from the camera and the slide projector will not be constant. Therefore, in order to obtain sharp pictures proper focusing should be achieved. This could be done manually or electronically using feedback mechanism.

To establish the feasibility of using moiré fringe topography and rasterstereography in gait analysis and to suggest means to devise a preliminary analytical description of children's gait in the age group 8 to 12 years old we conducted the following study (Siddiqui & Choudhry, 1990):

Apparatus. The apparatus used in the study is listed in Appendix D. In addition to the standard optical components the following were developed in our laboratory for the purpose of this study.

A *fine adjustment device* was used which was a plane sheet of cardboard mounted on a mechanical device similar to traveling microscope arrangement so that it could be moved over small distances. Moiré and raster grids were sharply focused on this plane. This was used as the reference plane in the rest of the photographing session. It was much easier to focus a subject walking on treadmill.

A *conic reference device* was constructed which was a right-circular cone. Dimensions of the cone (its depth as a function of height) were known. Moiré fringes formed on the cone can be used to calibrate the fringe pattern obtained during the gait cycle, because during normal walking it will not be possible to keep track of the distance of the subject from the camera which is essential to theoretically calculate the depth by counting the moiré fringes.

Location. The studies were conducted in Orthopaedic and Medical Institute as well as Bashir Hospital both located in Karachi.

The Work. A slide projector was placed at one end of a dark room and a healthy boy of age 9 years was asked to walk normally in its light. We projected a moiré grid (Fig. 3a) from a slide projector on the child's back and photographed the back using a 35 mm camera. Distance between the subject and the camera ranged between 324 & 395 cm. Camera was placed at a distance of 70 cm from the projector so that it directly faced the child. The line joining the camera lens and the projector lens must always be parallel to the frontal plane whenever moiré grid is projected. The procedure was repeated with a raster grid (Fig. 3b) placed in the slide projector. The fine adjustment device also acted as reference plane for rasterstereography. The camera was mounted on a tripod to avoid hand movements. As the boy walked, his photographs were taken at a rate of 5 frames per second with the help of a built-in automatic motor in the camera. A total of 4 film rolls of 36 exposures were used. Out of about 150 photographs obtained 8 snaps were studied giving the front and back view of the boy and showing the stances listed in Appendix E. Similar photographs were then taken of two female polio patients of ages 9 and 12 years respectively.




Fig. 3. Grids for (a) moiré fringe topography and (b) rastestereography




Fig. 4. Four phases of a single step.




Fig. 5. Layout for simultaneous moiré and raster recording.

Simultaneous Moiré and Raster Recording

A separate record using moiré fringe topography and rasterstereography for gait analysis is not of much use, because we are getting curvatures during one walking sequence and heights during the other walking sequence. A simultaneous recording with on-line data acquisition and processing capability is required if we want to model trunk asymmetries during movement

For simultaneous moiré and raster recording we use a 35 mm camera, 2 slide projectors, a moiré grid and a raster grid. Moiré grid is prepared in red color and raster grid prepared in blue color. Both the grids are simultaneously projected on the body using the two slide projectors which are placed as given in the layout of Fig. 5. After a color photograph was obtained a red filter matching with the color of the original

moiré grid was placed on it³. The red moiré grids became invisible and the blue raster grids appeared black. This was then fed in the scanner for analysis using rasterstereography algorithms. Similarly a blue filter matching with the color of the raster grid was placed on the picture. Raster was suppressed and the moiré grid appeared black. Then a standard black moiré grid was projected at the same angle to produce moiré fringes. Success of this procedure depends critically on proper matching of the colors.

DISCUSSION AND CONCLUSION

Moiré and raster techniques offer much scope in medical sciences. In the coming years they will supplement and possibly decrease the conventional X rays. The recent development of a procedure to obtain reproducible moiré pictures (Kamal, 1990; Kamal, Benoni & Willner, 1994) will increase the potential usefulness of this technique in the follow-up of spinal deformities as well as neurological disorders. Noninvasive 3-D optical techniques may find applications in the study of gait and movement analysis especially analysis of gymnastic performance. Moiré examination of spine may be useful in screening potential gymnasts and athletes (Akram & Kamal, 1991). There is a need to bring clinically relevant information which may provide diagnostic clues to the surgeon without taking the trouble to interpret the patterns or the results. For example, an algorithm which calculates and displays height asymmetries about the sagittal plane from moiré topographs and curvature asymmetries from rasterstereographs may be useful in screening and follow-up of scoliosis patients.

ACKNOWLEDGEMENTS

The authors would like to thank Mr. Salman Tahir who helped us with his great skill of photography. On the clinical side we received help from Dr. Raza Ali, Orthopedic Surgeon (A. O. Clinic, Karachi), Dr. Bashir A. Khan, Consultant Orthopedic Surgeon (Abbasi Shaheed Hospital, Karachi), Dr. Rahim, Orthopedic Surgeon, Dr. Sarwar, R. M. O. (Orthopedic & Medical Institute, Karachi). Last but not least we are indebted to our fellow members of Biomedical Physics Research Group, Bashir Ahmad and Umar F. Hashmi who were working on related projects (cf. Ahmad & Hashmi, 1990) and hence provided opportunity for interaction and critical evaluation of our work at every stage of the project.

APPENDIX A. Formulae for Height from Moiré Fringe Separation

a. For shadow type moiré apparatus the distance h_n from the n^{th} fringe to screen (the highest elevation must touch the screen) may be found from (Takasaki, 1974):

$$(A.1) \quad h_n = n \lambda [(d/s_0) - n]^{-1}$$

where λ = distance between the camera and the screen
 d = distance between the camera and the light source
 s_0 = screen interval (line thickness plus spacing)

³The idea of matching filters was suggested by ASC.

b. From the above the height difference between successive fringes in a shadow type apparatus may be calculated as (Kamal & Lindseth, 1980):

$$(A.2) \quad \Delta h = \lambda (d/s_0) [(d/s_0) - (n+1)]^{-1} [(d/s_0) - n]^{-1}$$

For U. S. A. studies (1980-82), we had $\lambda = 100$ cm, $s_0 = 1.0$ mm, $d = 50$ cm, which gave $\Delta h = 0.20$ cm for $n = 1$. For Karachi studies (1988-89), the parameters were $\lambda = 150$ cm, $s_0 = 1.4$ mm, $d = 110$ cm, which gave $\Delta h = 0.19$ cm for $n = 1$.

c. For the grating hologram type system developed by our group in Karachi the distance H_n from the n^{th} fringe as compared to the highest elevation is given by:

$$(A.3) \quad H_n = nM (M + 1) f P_0 (L - nMP_0)^{-1}$$

where M = magnification of the moiré grid
 f = focal length of the projector lens
 P_0 = moiré grid interval (line thickness plus spacing)
 L = distance between the camera and the projector lens

The above formula may be obtained by adapting the derivation of Suzuki, Yamashita, Yamaguchi & Armstrong (1981) for our system.

d. The height difference between successive fringes for our grating hologram system, therefore, may be expressed as:

$$(A.4) \quad \Delta H = M (M + 1) f (P_0/L) [1 - (n + 1)MP_0/L]^{-1} [1 - nMP_0/L]^{-1}$$

retaining only the linear term in P_0/L ($P_0 \ll L$). We had $L = 70$ cm $P_0 = 0.0242$ cm, $M = 18.15$, $f = 8.5$ cm, which gave $\Delta H = 1.04$ cm. The sensitivity may be increased by using finer grid (decreasing P_0), and using a lens of shorter focal length. Increasing L may produce distortions.

APPENDIX B. Formulae for Curvature Computation from Rasterstereographs

Let us suppose that a given raster grid on a plane surface (reference surface) has a periodic spacing equal to s . On the curved surface the spacing appears to be d . Let the portion of the curved surface under study may be the part of a great circle of radius ρ . Now, we have $s = \rho\phi$, where ϕ is the angle subtended by arc of length s . Therefore

$$(B.1) \quad \phi = s(1/\rho) = \kappa s$$

Also

$$(B.2) \quad d = \rho \sin\phi = \rho [\phi - (1/3!)\phi^3 + (1/5!)\phi^5 - \dots] = s [1 - (1/3!)\kappa^2 s^2 + (1/5!)\kappa^4 s^4 - \dots]$$

Since ϕ is small we neglect fourth and higher powers. Therefore

$$(B.3) \quad d/s = 1 - (1/3!)\kappa^2 s^2$$

which may be put in the form

$$(B.4) \quad \kappa = \pm (1/s) [6(1 - d/s)]^{1/2}$$

If $d = s$, $\kappa = 0$ and we have the condition of a flat surface.

APPENDIX C. Steps of Normal Gait

	<i>Right Leg</i>		<i>Left Leg</i>
Step 1	Right leg forward, left toe and right heel touching the ground. Center of gravity lying between the two feet.		
<i>Hip</i>	Extension	<i>Hip</i>	Extension
<i>Knee</i>	Extension	<i>Knee</i>	Extension
<i>Ankle</i>	Dorsiflexion	<i>Ankle</i>	Planter Flexion
Step 2	Right leg forward, right toe and right heel (that is, the right foot) and the left toe on the ground.		
<i>Hip</i>	Extension	<i>Hip</i>	Extension
<i>Knee</i>	Flexion	<i>Knee</i>	Flexion
<i>Ankle</i>	Neutral	<i>Ankle</i>	Neutral
Step 3	Left foot in the air (moving forward), body supported by right foot only. Center of gravity lying on top of right foot.		
<i>Hip</i>	Flexion	<i>Hip</i>	Flexion
<i>Knee</i>	Flexion	<i>Knee</i>	Flexion
<i>Ankle</i>	Neutral	<i>Ankle</i>	Neutral
Step 4	Left leg forward, right toe and left heel touching the ground. Center of gravity lying between the two feet		
<i>Hip</i>	Extension	<i>Hip</i>	Extension
<i>Knee</i>	Extension	<i>Knee</i>	Extension
<i>Ankle</i>	Planter Flexion	<i>Ankle</i>	Dorsiflexion

APPENDIX D. Apparatus Used in the Study

<i>Apparatus</i>	<i>Specifications</i>
Camera	NIKON MODEL EM (body only)
Zoom Lens	NIKKOR-F
	Focal length 50-135 mm (1:3.5)
Film Rolls	a) KODAK TMAX, ASA 400, B&W
	b) KODAK TMAX, ASA 3200, B&W
Projector	Make GRIFFIN & GEORGE (UK)
	Lamp 24 V, 150 W, TUNGSTEN HALOGEN 1.9 AMPS
	Lens 85 mm
Video Camera	National, Model M5
Fine Adjustment Device	(described in the text)
Conic Reference Device	(described in the text)

APPENDIX E. Anatomical Terms

I. Directional Terms

Superior: *A is superior to B* means A is nearer to the head than B.

Inferior: *B is inferior to A* means A is superior to B.

Medial: *B is medial to A* means B is closer to the midline than A.

Lateral: *A is lateral to B* means B is medial to A.

Proximal: *C is proximal to D* means C is nearer to attachment point of a limb than D.

Distal: *D is distal to C* means C is proximal to D.

Anterior: *Anterior point* is a point which is nearer to or in front of the body.

Posterior: *Posterior point* is a point which is nearer to or at the back of the body.

The above terms are relative. They are used to compare any two arbitrary points on the body.

II. Cardinal Planes

Sagittal: Vertical plane dividing the body into left and right portions.

Frontal: Vertical plane dividing the body into anterior and posterior parts.

Transverse: Horizontal plane dividing the body into superior and inferior parts.

These planes remain the same regardless of body orientation with respect to earth.

III. Anatomical Axes

Transverse: Normal to sagittal plane through the body from side to side.

Longitudinal: Normal to transverse plane through the body from top to bottom.

Anteroposterior: Normal to frontal plane through the body from front to back.

REFERENCES

- Adair, I. V., van Wijk, M. C. & Armstrong, G. W. D., (1977) Moiré topography in scoliosis screening. *Clin. Orthop.* 129: 165-171
- Ahmad, B. & Hashmi, U. F. (1990) To develop different techniques to study spinal deformity, *M. Sc. Project, Univ. Karachi* (unpublished)

Akram, M., (1989) Construction of a shadow type moiré apparatus. *M. Sc. Project*, Univ. Karachi (unpublished)

Akram, M. & Kamal, S. A. (1991) Role of moiré fringe topography in the skeletal examination of school athlete, *International Congress and Exposition on Sports Medicine and Human Performance*, Vancouver, Canada (poster presentation)^u

El-Sayyad, M. M. & Kamal, S. A., (1981) Cobb's angle measurement by moiré topographs. *Proc. 34th Ann. Conf. Eng. Med. Biol.* **23**: 311^v

Hierholzer, E. & Frobin, W., (1981) Rasterstereographic measurement and curvature analysis of the body surface of patients with spinal deformities. In: *Moiré Fringe Topography and Spinal Deformity*, [Proceedings of the 1st International Symposium, Burlington, Vt., 1979, U. S. A.], (Ed. M. S. Moreland, M. H. Pope & G. W. D. Armstrong), pp. 267-276, Pergamon, New York

Kamal, S. A., (1983) Determination of degree of correction of spinal deformity by moiré topographs. In: *Moiré Fringe Topography and Spinal Deformity*, [Proceedings of the 2nd International Symposium, Münster, Germany, 1992], (Ed. B. Drerup, W. Frobin & E. Hierholzer), pp. 117-126, Gustav Fischer, Stuttgart^y

Kamal, S. A., (1987) Moiré topography for the study of multiple curves of spine. In: *Surface Topography and Spinal Deformity*, [Proceedings of the 4th International Symposium, Mont Sainte Marie, Québec, Canada, 1986], (Ed. I. A. F. Stokes, J. R. Pekelsky & M. S. Moreland), pp. 43-50, Gustav Fischer, Stuttgart & New York^e

Kamal, S. A., (1990) Reproducibility of moiré topographs. In: *Surface Topography and Body Deformity*, [Proceedings of the 5th International Symposium, Vienna, Austria, 1988], (Ed. G. Windischbauer & H. Neugebauer), pp. 151-153, Gustav Fischer, Stuttgart & New York^o

Kamal, S. A. (1996a) A 3-D static model of the human spinal column. *Kar. U. J. Sc.* **24**: 29-34^v

Kamal, S. A. (1996b) 3-D dynamic modelling of the human spinal column. *21st International Nathiagali Summer College on Physics and Contemporary Needs*, Nathiagali, Pakistan^o

Kamal, S. A., Benoni, G. & Willner, S., (1994) A study to test the reproducibility of moiré topographs. *Kar. U. J. Sc.* **22**: 67-74^o

Kamal, S. A. & El-Sayyad, M. M., (1981) The use of moiré topographs for the detection of orthopedic defects in children of age group four to seven years. *Med. Phys.* **8**: 549*

Kamal, S. A., Bukhari, N. & Akram, M. (1990) A comparison of back moiré topographs of children in the sitting and standing positions. In: *Surface Topography and Body Deformity*, Proc. 5th Int. Symp., loc. cit., pp. 77-78^o

Kamal, S. A. & Lindseth, R. E., (1980) Moiré topography for the detection of orthopedic defects. *Periodic Structures, Gratings, Moiré Patterns and Diffraction Phenomena*, Proc. Soc. Photo-Opt. Instr. Eng. **240**: 93-295^u

Lane, H. R., (1983) Photogrammetry in medicine. *Photogr. Eng.* **49**: 1453-1456

Lewis, C. G., Moreland, M. S. & Pope, M. H., (1981) Moiré fringe topography in gait analysis: a methodologic evaluation. In: *Moiré Fringe Topography and Spinal Deformity*, Proc. 1st Int. Symp., loc. cit., pp. 81-86

^u Abstract: <https://www.ngds-ku.org/Presentations/Skeletal.pdf>

^v Full text: <https://www.ngds-ku.org/Papers/C12.pdf>

^y Full text: <https://www.ngds-ku.org/Papers/C23.pdf>

^e Full text: <https://www.ngds-ku.org/Papers/C26.pdf>

^o Full text: <https://www.ngds-ku.org/Papers/C34.pdf>

^v Full text: <https://www.ngds-ku.org/Papers/J18.pdf>

^o Abstract: <https://www.ngds-ku.org/Presentations/Dynamical.pdf>

^o Full text: <https://www.ngds-ku.org/Papers/J15.pdf>

* Full text: <https://www.ngds-ku.org/Papers/C11.pdf>

^o Full text: <https://www.ngds-ku.org/Papers/C33.pdf>

^u Full text: <https://www.ngds-ku.org/Papers/C08.pdf>

Siddiqui, Y. A. & Choudhry, A. S., (1990) Gait analysis using moiré fringe topography and rasterstereography. *M. Sc. Project*, Univ. Karachi (unpublished)

Shochat, S. J. & Csongradi, J. J., (1983) Moiré phototopography in the evaluation of anterior chest wall deformity. In: *Moiré Fringe Topography and Spinal Deformity*, Proc. 2nd Int. Symp., loc. cit., pp. 249-256

Stüben, K., (1992) Multigrid strategies - applications and techniques. *17th International Nathiagali Summer College on Physics & Contemporary Needs*, Nathiagali, Pakistan

Suzuki, M., Kanaya, M., Suzuki, K. & Shokouchi, N., (1981) Projection type moiré topography camera (FM 40) system used for early detection of scoliosis. In: *Moiré Fringe Topography and Spinal Deformity*, Proc. 1st Int. Symp., loc. cit., pp. 24-39

Suzuki, N., Yamashita, Y., Yamaguchi, Y. & Armstrong, G. W. D., (1981) Measurement of posture using moiré topography. In: *Moiré Fringe Topography and Spinal Deformity*, Proc. 1st Int. Symp., loc. cit., pp. 121-131

Takasaki, H. (1979) The development and the present status of moiré topography. In: *Holography in Medicine and Biology*, Proceedings of the International Workshop, Münster, Germany (Ed. G. von Bally), pp. 45-59, Springer, Berlin, Heidelberg & New York

Willner, S., (1979) Moiré topography for the diagnosis and documentation of scoliosis. *Acta Orthop. Scand.* 50: 295-302

Windischbauer, G., (1983) Moiré topography as an optical tool in anthropometry. In: *Moiré Fringe Topography and Spinal Deformity*, Proc. 2nd Int. Symp., loc. cit., pp. 201-205

Yoshino, Y., Tsukiji, M. & Takasaki, H., (1976) Moiré topography by means of a grating hologram. *Appl. Opt.* 15: 2414-2417


ADDITIONAL NOTES (related to this paper, but not part of the published manuscript)

Correction on page 15 —
Appendix C: Steps of Normal Gait

Step 2: Right leg forward, right toe and right heel (that is, the right foot) touching the ground as well as the left toe on the ground.

Normal gait should be studied using moiré fringe topography, rasterstereography and video-recording with the child attired solely in white, exercise (gym) briefs (which are form fitting), barefoot, stripped to waist — see figure on right. A much-clearer diagram of the concepts elaborated in Fig. 3 and 5, which appears in the document: *3-D-spinal-column-surface analysis (height and curvature maps) by combining moiré fringe topography and rasterstereography with backscatter-X-ray-scanning technology*, reproduced on the extreme right from the following

link: <https://www.ngds-ku.org/Presentations/Backscatter.pdf>



Web address of this document (first author's homepage): <https://www.ngds-ku.org/Papers/J16.pdf>

CONTENTS

Physical Sciences Section

<i>SHAMIM FARHAT, S. YOUSUF HAIDER AND M. ATAULLAH KHAN</i> SIMULTANEOUS LIQUID CHROMATOGRAPHIC DETERMINATION OF ORGANOPHOSPHORUS AND SYNTHETIC PYRETHROID INSECTICIDES IN LIQUID FORMULATIONS	1-5
<i>SYED ARIF KAMAL, A. S. CHOUDHRY AND Y. A. SIDDIQUI</i> GAIT ANALYSIS USING MOIRE FRINGE TOPOGRAPHY AND PRIVATE RASTERSTEREOGRAPHY (SIMULTANEOUS RECORDING)	7-18
<i>N. BANO</i> DYNAMIC PROPERTIES OF HUMID INSULATING SURFACES	19-32
<i>MIRZA ANEES AHMAD AND ANWAR JAMAL</i> EFFECT OF TEMPERATURE ON THE STABILITY OF CEPHRADINE DIHYDRATE SUSPENSION	33-34
<i>ISMAT ALI AND M.A. BASIT</i> SOME STUDIES ON BIOMASS AS FUEL	35-39
<i>MUHAMMAD ALI PARACHA</i> A CHARACTERIZATION FOR A SKEW-FIELD AND HO_2 (R_0 , Q/Z)	41-42
<i>RANA KHALID NAEEM</i> EXACT SOLUTIONS FOR AN INCOMPRESSIBLE SECOND - GRADE FLUID FLOW EQUATIONS	43-52
<i>SYED ARIF KAMAL</i> COMBINATION OF MOIRE CONTOURS AND EDGE-BASED ALGORITHM PRIVATE TO STUDY MOTION IN THE SAGITTAL PLANE	53-59
<i>SYED AFROZUDDIN AHMED, EHTESHAM HUSSAIN, ANWER KHURSHID</i> ON AN ALTERNATIVE FORMULA TO FIND MODE OF TWO PARA-METER GAMMA DISTRIBUTION	61-65
<i>M.A. MALIK</i> THE ESTIMATION OF PARITY WITH THE MAKEHAMS CURVE FITTING	67-79
<i>GHULAM HUSSAIN, S.M. AQIL BURNEY AND ASIM J. SIDDIQUI</i> MOMENTS OF POLYA-EGGENBERGER DISTRIBUTION USING FINITE DIFFERENCE CALCULUS	81-84
<i>AHMAD SAEED AKHTER AND SHAHID KAMAL</i> THE EFFECT OF TRUNCATION ON PRECISION AND ACCURACY IN THE MAXIMUM LIKELIHOOD ESTIMATION OF THE PARAMETERS OF NORMAL POPULATIONS FROM SINGLY-TRUNCATED SAMPLES	85-88
<i>ASIM JAMAL SIDDIQUI</i> KARACHI CITY POPULATION PROJECTION	89-94
<i>T. RAHIM AND A. GHANI</i> QUANTUM THEORY OF CIRCULAR CYLINDERS	95-102

Biological Sciences Section

<i>RAFAT AMIR, JUNAID MAHMOOD ALAM AND M.A. JABBAR</i> ISOLATION AND BIOLOGICAL PROPERTIES OF SCORPION VENOM PROTEINS (II) COMPARATIVE STUDY OF THREE TOXINS WITH ACETYLCHOLINESTERASE ACTIVITY ISOLATED FROM THE VENOM OF <i>LYCHAS LAEVIFORN</i>	103-113
<i>AISHA NAZLI, MAHMOOD AKHTAR, M. ALTAF KHAN</i> RAPID IDENTIFICATION OF MYCOPLASMA BY IMMUNOFLUORESCENCE TECHNIQUE	115-120
<i>REHANA VAHIDI, FARRUKH JAHAN AND RIZWANA B. NASIM</i> THE OCCURRENCE OF <i>LISTERIA</i> SPP. IN FOOD AND FODDER SAMPLES IN PAKISTAN	121-127
<i>SHEIKH AJAZ RASOOL AND RASHID ALI</i> NOVEL MODE OF ERROR-FREE REPAIR OF NITROSOGUANIDINE MEDIATED ALKYLATION IN <i>SACCHAROMYCES CEREVISIAE</i>	129-133
<i>S. AMINULAH KHAN AND S.N.H. NAQVI</i> LABORATORY TESTS ON THE EFFICACY AND PENETRATION OF PHOSPHINE AGAINST <i>T. CASTANEUM</i> HERBST AT VARIOUS TEMPERATURES AND RELATIVE HUMIDITIES	135-140
<i>N. AHMED, N. AFTAB, S.A. SIDDIQUI, S.M. ALI, H. ASKARI, H. HUSSAIN</i> BIOCHEMICAL STUDIES ON THE NEUROTOXICITY OF ENVIRONMENTAL POLLUTANTS PART-I ASSESSMENT OF METAL CONTENT IN HAIR SAMPLES FROM INDUSTRIAL AND RESIDENTIAL AREAS OF PAKISTAN	141-144
<i>R. ARSHAD, N.M. QURESHI, S.I. BURNEY, U. SIDDIQUI AND MASOOD A. QURESHI</i> EVALUATION OF SINGLE PROGESTERONE ASSAY FOR PROPER LUTEAL FUNCTION IN A NORMAL MENSTRUAL CYCLE	145-150
<i>SALEHA HASNI AND S. NAZRUL-HASNAIN, V.U. AHMAD, SHAISTA KHATOON, VIQAR SULTANA, SHAIQ ALI AND USMANGHANI KHAN</i> ISOLATION AND CHARACTERIZATION OF FATTY ACIDS, HYDROCARBONS AND STEROLS OF <i>CLADOPHORA GLOMERATA</i> OF HUB VALLEY AREA OF KARACHI	151-160
<i>MOAZZAM ALI KHAN, MAHMOOD AKHTAR, AISHA NAZLI AND M. ALTAF KHAN</i> VARIATION IN OXYGEN PRODUCTION IN WASTE STABILIZATION PONDS AT THE KARACHI UNIVERSITY CAMPUS	161-169
<i>SHAMEEM ARA SIDDIQUI, ABDUL BARI AND MUHAMMAD ASIF</i> PREVALENCE OF ENTEROTOXICOGENIC <i>STAPHYLOCOCCUS AUREUS</i> IN VEGETABLES AND FRUITS	171-176
<i>SOALEHA AHMED, FOUZIA ISMAIL AND HAJRA AZHAR ALI</i> DIFFERENCES IN FREE PHENOLIC ACID CONTENT IN RESISTANT AND SUSCEPTIBLE VARIETIES OF <i>TRITICUM AESTIVUM</i> AFTER INFECTION BY BROWN RUST FUNGUS, <i>PUCCINIA RECONDITA</i>	177-182
<i>R.K. DHAWAN, R.K. PUROHIT, R.K. CHAUDHARY AND M.L. GUPTA</i> GAMMA RADIATION INDUCED CHANGES IN INTESTINE OF <i>PASSER DOMESTICUS</i> LINN	182-187