

Paper presented during *the Second Conference on Athromathematics and Sport Mathematics in the Memory of (Late) Hussain Ahmed Bilgirami (ANTHROMATHEMATICS 2014)*, Department of Mathematics, University of Karachi, Karachi, Pakistan and Government College, Hyderabad, Pakistan, Thursday, September 4, 2014 (1315h-1330h, Assembly Hall, Govt. College), Technical Session Anthro14-II, abstract#Anthro14-06, p 10

## Crystal-Structure-Concept-Based Modeling of the Human Spinal Column Validated through 3-D-Bone Scanning

Syed Arif Kamal<sup>†,\*</sup>, Maqsood Sarwar<sup>†</sup> and M. Khalid Rajput<sup>§</sup>

SF Growth-and-Imaging Laboratory, Anthromathematics Group, Departments of <sup>†</sup>Mathematics and <sup>§</sup>Physics, University of Karachi, Karachi 75270, Pakistan; <sup>†</sup>sakamal@uok.edu.pk

Spinal column, being a 3-D structure, is not completely visualized in ordinary anteroposterior (AP) X rays, which show spinal projection in the frontal plane. Hence, such X rays do not display kyphosis or lordosis. 3-D-spinal models were able to generate full views from projections of spine in the frontal and the sagittal planes obtained from AP- and lateral-X-ray pictures or moiré topographs of patients in the attention position. A parabolic curve was generated from moiré measurements,  $x = x(\xi)$ ,  $y = y(\xi)$ ,  $z = z(\xi)$ , best fitted to discrete measurements performed at locations of 33 vertebrae of spinal column,  $\xi_i$ ;  $i = 1, \dots, 33$  (cervical, thoracic, lumbar and sacral regions). Rotation of coördinate system through a suitable angle made the cross term ( $yz$ ) vanish and represented curvatures as double the coefficients of squares of  $y$  and  $z$ . These curvatures were used to define degree of correction of spinal deformity (<http://www.ngds-ku.org/Papers/J18.pdf>). This 3-D-static model was used to study children's postures. The dynamic model was constructed by including spinal-column movements during a gait cycle, linking spinal column in the anatomical position to the first phase of gait cycle (<http://www.ngds-ku.org/Papers/J16.pdf>) through edge-based algorithm (<http://www.ngds-ku.org/pub/confabst0.htm#C42>). The procedure was repeated to link first phase to the second phase and so on. To construct a vertebral-level model, spinal column was visualized as a crystal structure (<http://www.ngds-ku.org/Presentations/BZU1.pdf>). The center-of-mass of each vertebra was expressed in terms of positional coördinates in the body-coördinate system, just like *form factor* in crystallography. The surface structure of each vertebra could be studied using moiré fringe topography, which gives 3-D-coördinate information (<http://www.ngds-ku.org/Presentations/Moire.pdf>) and rasterstereography, which gives curvature information (<http://www.ngds-ku.org/Presentations/Rasterstereography.pdf>). Combined with rotational (in terms of Euler angles) as well as inter-vertebral-spacing information, such an analysis may be considered equivalent to *structure factor*, determined by crystallographers. In order to study the vertebrae of spinal column of a live human being (without cutting open to reach vertebral surface to study using stereophotogrammetric techniques), *bone-surface-structure scanning* was introduced on May 30, 2013 (<http://www.ngds-ku.org/Presentations/Backscatter.pdf>) by the first author and elaborated in the Syed Firdous memorial lecture (<http://www.ngds-ku.org/Presentations/Scan.pdf>), expanding upon the backscatter-body-scanning system, employed for passenger security screening at airports (<http://www.ngds-ku.org/Presentations/Security.pdf>). Increasing the intensity of backscatter-X rays enough to reach to the bone surface and projecting these X rays through a moiré (<http://www.ngds-ku.org/Papers/C68.pdf>) or a dotted-raster grid (<http://www.ngds-ku.org/Papers/J31.pdf>), vertebral surfaces could be studied by generating their height and curvature maps. In *grating-hologram-type-backscatter moiré* passive (post-recorded) correction (for misalignment or rotation) was possible. A projected-dotted-raster grid (X rays blocking raster patterns) generated 3-D-curvature map of the spinal column. Holographic images could be generated by recording and processing multiple images in the semi-circular angular range. As regards radiation damage, backscatter-X rays reflected off the bone surface and were not absorbed in its material, it was assumed that there would not be so much damage as from regular-X rays, provided eyes and gonads are, properly, shielded. Discretion is advised, while using these techniques in high-risk groups. Using techniques from physics (image projection/recording), computer science (edge-based and intensity-based algorithms) and information technology (image processing), stereophotogrammetric imaging of humans using moiré fringe topography, dotted-rasterstereo-graphy, raster stereophotogrammetry (<http://www.ngds-ku.org/Presentations/Anthroimaging.pdf>), edge-based moiré and edge-based dotted-raster have the potential to open up new horizons in 3-D imaging of human-skin, -bone and -organ surfaces (sectional-semicircular views) as well as their infinitesimal movements.

**Keywords:** Human spinal column, static model, dynamic model, crystal-structure-based model, moiré fringe topography, dotted-rasterstereography, backscatter-X-ray scanning

**Conflict of Interest Statement:** No potential conflict of interest is identified for this work

**Web address of this document:** <http://www.ngds-ku.org/Presentations/Spinal.pdf>

**HTML version:** <http://www.ngds-ku.org/pub/confabstB.htm#C123>:

**Reprinted from:** <http://www.ngds-ku.org/Athromathematics/2014/Abstracts2014.pdf>

\*Prof. Dr. Syed Arif Kamal (<http://ngds-ku.org/kamal>), PhD (Mathematical Neuroscience), MA, Johns Hopkins, Baltimore, MD, United States, MS, Indiana, Bloomington, IN, United States, Associated Professor in Orthopedic Surgery, Malmö General Hospital, Sweden (1988), Research Associate in Orthopedic Surgery, James Whitecomb Riley Hospital for Children, Indianapolis, IN, United States (1980) and Member, Subject Committee for Physical Education, Health and Sport Sciences, National Testing Service (<http://nts.org.pk>), Islamabad, Pakistan; *Paper Mail:* Professor and Chairman, Department of Mathematics (<http://math.uok.edu.pk>), and Project Director, the NGDS Pilot Project (<http://ngds.uok.edu.pk>), University of Karachi (<http://www.uok.edu.pk>), Karachi 75270, Pakistan; *Telephones:* +92 21 9926 1300-6 ext. 2380, 2293